

INTRODUCTION - LattePanda 3 Delta

LattePanda 3 Deltaシングルボードコンピュータは、優れたパフォーマンスのために2.5Gイーサネットポートを新たに搭載しています！

ITEM NAME

SPECIFICATION

PRODUCT No

1)LattePanda 3 Delta 864 - The Fastest Pocket-sized Windows/Linux Single Board Computer (8GB RAM/64GB eMMC)



*Processor: Intel® Celeron® N5105
*CPU: 2.0~2.9GHz Quad-Core, Four-Thread
*Graphics: Intel® UHD Graphics (Frequency: 450 - 800MHz)
*Memory: LPDDR4 8GB 2933MHz
*Storage: 64GB eMMC V5.1
*Expansion Slots:
1x M.2 M Key (2280), PCIe 3.0 2x, Supports NVMe SSD
1x M.2 B Key (2242/2252/2280), USB 2.0, USB 3.0, SIM, SATA
(Option support PCIe 3.0 1x), Supports 4G & 5G module
*Network Connectivity:
1x Wi-Fi 6 @ 2.4GHz & 5 GHz (160MHz)
1x Bluetooth 5.2
1x Intel 2.5 Gigabit Ethernet
*USB Ports:
2x USB 3.2 Gen1 Type A
1x USB 3.2 Gen2 Type A
1x USB Type C, Supports PD, DP, USB 2.0
1x USB 2.0 Pin Header
*Display:
1x HDMI 2.0b: Up to 4096x2160 @ 60Hz HDR
1x DP 1.4: Up to 4096x2160 @ 60Hz HDR
1x eDP: 30 Pins, 2 lanes, Extendable Touch Displays up to 1920*1080

型番:DFR0981

*TPM: built-in TPM (2.0)
*Co-processor: Arduino Leonardo ATMEGA32U4
*Audio: Microphone + Headphone Combo Connector
*GPIO & Other Features:
Up to 12x Analog Inputs
Up to 20x Digital Input/Output (7 PWM)
1x UART
1x I2C
1x SPI
1x Audio Header
1x RS232 Header
1x USB 2.0 Header
1x Fan Port (4 Pins, 1.25mm, PWM, 5V)
1x 4-Pin Header (Power and Switch)
*OS Support: Windows 10 & Windows 11 & Linux
*Input Power:
PH2.0 - 4Pin DC Input: 12V
USB Type-C PD Input: 15V DC
*RTC Battery: CR927
*Dimension: 125 x 78 x 16mm
*Operating Temperature: 0°C~60°C
*Certification: CE, FCC, KC, RoHS

2)LattePanda 3 Delta 864 - The Fastest Pocket-sized Windows/Linux Single Board Computer with Win10 Enterprise License (8GB/64GB)



CPU: Intel® Celeron® N5105
Core: 2.0~2.9GHz Quad-Core, Four-Thread
Graphics: Intel® UHD Graphics (Frequency: 450 - 800MHz)
Memory: LPDDR4 8GB 2933MHz
Storage: 64GB eMMC V5.1
Expansion Slots:
1x M.2 M Key, PCIe 3.0 2x, Supports NVMe SSD
1x M.2 B Key, USB 2.0, USB 3.0, SIM, SATA(Option support PCIe 3.0 1x), Supports 4G & 5G module
Connectivity:
1x Wi-Fi 6 @ 2.4GHz & 5 GHz(160MHz)
1x Bluetooth 5.2
1x Intel 2.5 Gigabit Ethernet
USB Ports:
2x USB 3.2 Gen1 Type A
1x USB 3.2 Gen2 Type A
1x USB Type C, Supports PD, DP, USB 2.0
1x USB 2.0 Pin Header

型番:DFR0982

Display:
1x HDMI 2.0b: Up to 4096x2160 @ 60Hz HDR
1x DP 1.4: Up to 4096x2160 @ 60Hz HDR
1x eDP: Extendable Touch Displays up to 1920*1080
TPM: built-in TPM(2.0)
Co-processor: Arduino Leonardo ATMEGA32U4
Audio: Microphone + Headphone Combo Connector
GPIO & Other Features:
12x Analog Inputs*
Up to 23x Digital Input/Output (7 PWM)*
1x UART
1x I2C
1x SPI
1x Audio Connector
1x 4-Pin RS232 Header
1x Fan Port (4 Pin 1.25mm PWM 5V)
1x 4-Pin Header (Power and Switch)
OS Support: Windows 10 & Windows 11 & Linux
Dimension: 125 x 78 x 16mm
Operating Temperature: 0°C~75°C