

## Camera

	<p><b>Feature:</b></p> <ul style="list-style-type: none"> <li>✧ 1/3" Sony 2.4 M Exmor Sensor</li> <li>✧ Full HD 1920x1080P@25/30fps (AHD)</li> <li>✧ Color:0.05Lux@F1.2, B/W:0.02Lux@F1.2, Sense-up:0.001Lux@F1.2</li> <li>✧ Smart DNR, 3D/2D DNR, Sense Up, Fog Reduction</li> <li>✧ Simultaneous Video output: AHD and CVBS (Composite)</li> </ul>
---	--

<b>MODEL</b>	<b>AV-SAHC321M</b>
Image Sensor	1/3" Sony 2.4 Megapixel Exmor CMOS Sensor
Video Frame Rate (Maximum)	1920x1080P@25/30fps, 1280x720P@30fps
Minimum Illumination	Color:0.05Lux@F1.2, B/W:0.02Lux@F1.2, Sense-up:0.001Lux@F1.2
Wide Dynamic Range	90dB
Video Output	Simultaneous Video Output, AHD and CVBS (Composite)
Mechanical IR Cut Filter	Yes
Audio	N/A
IR LED; Working Distance	N/A
OSD Menu	OSD Control / CoC (Via the coax)
Day&Night Mode	Color / B&W / Auto / IR Sync
Auto Electronic Shutter	1/25(30)~1/30, 000 sec; Flickerless
Manual Electronic Shutter	1/25(30), 1/50(60),1/100(120), 1/240, 1/500, 1/1000, 1/2000, 1/4000, 1/8000, 1/16000, 1/30000 Sec
White Balance	ATW / AWB / PWB (Push Lock) / Manual
WDR; BLC; HLC	High (Max 90dB) / Middle / Low / Off; Program; On / Off One cable Version without WDR Function
Fog Reduction	Auto / Manual / Off ; Level: High / Middle / Low
Dynamic Noise Reduction	High / Middle / Low / Off
Sense Up	On (x2, x4, x8, x16, x32) / Off
Language	English, Japanese, Traditional Chinese, Simplified Chinese
E-Zoom	1.0x~8.0x (Step 0.1)
Image Setting	Sharpness / Mirror / Flip

Privacy Zone Mask	16 Zones Programmable
Motion Detection	On: Sensitivity, Programmable / Off
Lens Shading Compensation	On / Off
Automatic IRIS; Connector	DC; D4 IRIS Jack
Lens Adapter	Built-in Varifocal Lens
Lens	N/A
Lens Option	N/A
Water Resistance	N/A
Max. Breaking Strength	N/A
Power Supply; Consumption	12Vdc: 1.2W; 12Vdc/24Vac: 8.2W, PoC (Option)
Operation; Storage Temp.	-10°C ~ 50°C; -20°C ~ 60°C
Operation; Storage Humidity	Maximum: RH80%; RH90%
Dimensions	62(W)x56(H)x120(L)mm
Net Weight	350g