

## DVR

	<p><b>Feature:</b></p> <ul style="list-style-type: none"> <li>◇ Max to 3840 * 2160 @ 30/25 fps</li> <li>◇ DUHD</li> <li>◇ H.265</li> </ul>
---	--

<b>MODEL</b>		<b>4K2KDVR-0815A</b>
Video	Input	8CH AHD(support 2CH 4K2K)
	Output	Max. 3840 x 2160 1 HDMI with Audio
Audio	Input	4
	Output	1
System	Operating System	Embedded Linux OS
	Video Decoding format	H.265
	SATA Devices	Max. 1 x SATA Devices (HDDx1)
	External HDD	N/A
	Alarm In / Relay Out	Alarm-in x 8 Relay-out x 1
	Serial Interface	RS-485
	USB 2.0 Ports	USB2.0 X 2
	Dimension ( mm )	280(w)x51(h)x203(d)
	Power Rating	12V 3A ,36W
Display	Split Screen	1, 4, 9, SEQ.
Recording	Recording Throughput (60Hz /50Hz DUHD Camera)	352 x 288, 704 x 576, 944 x 576(PAL) 352 x 240, 704 x 480, 944 x 480(NTSC) 1280 x 720 @ 30/25 fps 1920 x 1080 @ 30/25 fps 2018 x 1524 @ 30/20 fps 2592 x 1520 @ 30/20 fps 2592 x 1944 @ 30/20 fps Max. 3840 * 2160 @ 30/25 fps
	Mode	Continuous, Event, Schedule
Playback	Search Mode	Date/time, Event

	Zoom	*Digital ( x2 ~ x5 )
Network	Network Interface	10/100 Ethernet
	Protocol	TCP/IP, SMTP, HTTP, DHCP, PPPoE(ADSL), NTP, DDNS
	Remote Software	SoCatch, IE Browser, iCMS Pro
	Account	1 Admin + 10 Users
	Mobile Device	IOS & Android
Backup	Interface	USB or SATA
	Audio Backup	YES
	Backup Type	Network, ext. USB flash device , SATA optical DVD..etc.
Alarm	Event Log	Up to the 10000 events
OSD & DVR	Multi-Language	Supported
	System Upgrade	USB Flash Drive, iWatch DVR
General	Operating Temperature:	0°C ~ +55°C (32°F ~ 131°F)
	Operating Humidity:	10%~80%